

PROPERTY ARMOR

PRO Series P2 Slammer Mini Split

Notched Corner Height 24" - 42" Typica 1/4" x 1.75 Lock Shroud Mounting Flange Anchor Ports x4 1/2" Diameter Typical

MATERIAL

Frame

1.5" x 1.5" x 1/8" Steel Angle Iron Base Flange 1.5" with 1/2" Anchor Hole on Four Sides

Center and Top Reinforcement Band 1.5" x 1/8" Steel Flat Bar

Expanded Metal

3/4 #13 Flat Expanded Metal

Powder Coated Satin Black

Construction:

MIG Welded Filet .035 E71T-GS A5.20

Lock Housing 4"RD x 1/4"- Accepts STD Puck Lock Hinge Pins 1/2" Round Stock / Barrels 1/2" RD

DIMENSIONAL DATA

Application Specific

FEATURES

Date Submitted:

Notched Corner for Easy Installation Around Line Set Expanded Metal Helps Prevent Unauthorized Intrusion Can Be Anchored In The Ground or To A Concrete Pad Heavy Duty Lock Housing for added Intrusion Prevention

Job Name:		
Location:		
Engineer:		
Contractor:		

www.PropertyArmor.net Toll Free 855-858-5757

904-356-0093 ш 904-356-0092 屲 32254 교 JACKSONVILLE, STREET BEAVER 2910-4 WEST PROPERTY ARMOR